

Stahlrohre schwarz nahtlos - Normalwand

nach EN 10216-1/ EN 10220, Qualität P235TR2
in Werkslängen á ca. 6 m, mit glatten Enden

| Ø | Wandstärke in mm | | | | | | | |
|-------|------------------|-----|-----|-----|-----|-----|-----|-----|
| | 2,6 | 2,9 | 3,2 | 3,6 | 4,0 | 4,5 | 5,0 | 6,3 |
| 30,0 | ✓ | | | | | | ✓ | |
| 33,7 | ✓ | | | | | | ✓ | |
| 38,0 | ✓ | | | | | | | |
| 42,4 | ✓ | | | | | | | |
| 44,5 | ✓ | | | | | | | |
| 48,3 | ✓ | | | | | | | |
| 51,0 | ✓ | | ✓ | | | | | |
| 57,0 | | ✓ | | | | | | |
| 60,3 | | ✓ | | | | | | |
| 70,0 | | ✓ | | | | | | |
| 76,1 | | ✓ | | | | | | |
| 82,5 | | | ✓ | | | | | |
| 88,9 | | | ✓ | | | | | |
| 101,6 | | | | ✓ | | | | |
| 108,0 | | | | ✓ | | | | |
| 114,3 | | | | ✓ | | | | |
| 133,0 | | | | | ✓ | | | |
| 139,7 | | | | | ✓ | | | |
| 168,3 | | | | | | ✓ | | |
| 273,0 | | | | | | | | ✓ |

Stahlrohre schwarz nahtlos - Starkwand

nach 10216-3 P355N(TC1), EN 10210 S355J2H und DIN1629 ST52.0
in Werkslängen á ca. 6 m, mit glatten Enden

| Ø | Wandstärke in mm | | | | | | | | | |
|-------|------------------|-----|-----|-----|-----|-----|-----|-----|------|------|
| | 2,9 | 3,2 | 3,6 | 4,0 | 5,0 | 6,3 | 7,1 | 8,0 | 10,0 | 12,5 |
| 30,0 | ✓ | | | ✓ | | | | | | |
| 38,0 | | ✓ | | ✓ | ✓ | | | | | |
| 42,4 | | | | | ✓ | ✓ | | | | |
| 44,5 | | | | | | | | ✓ | | |
| 48,3 | | | ✓ | | ✓ | ✓ | | | | |
| 51,0 | | | | | | ✓ | | | | |
| 57,0 | | | | ✓ | | | | | | |
| 60,3 | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | |
| 63,5 | | | | ✓ | | | | ✓ | | |
| 70,0 | | | | ✓ | ✓ | | | | ✓ | ✓ |
| 76,1 | | | ✓ | ✓ | ✓ | ✓ | | | ✓ | |
| 82,5 | | | | | ✓ | | | | | |
| 88,9 | | | | | ✓ | ✓ | | ✓ | | ✓ |
| 101,6 | | | | | ✓ | ✓ | | | ✓ | |
| 108,0 | | | | | ✓ | | | | | |
| 114,3 | | | | | ✓ | ✓ | ✓ | | ✓ | ✓ |

✓ = lagernd
leer = auf Anfrage