

Rundstahl

nach EN 10083

Qualität C45E/C45R (1.1191/1.1201) gewalzt nach EN 10060 Stangenlänge ca. 4,5 – 6,5 m				Qualität C45E+N (1.1191) geschmiedet n. DIN 7527 Stangenlänge ca. 4 - 6 m			
∅		∅		∅		∅	
20	✓	145	✓	300	✓	550	✓
25	✓	150	✓	310	✓	560	✓
30	✓	155	✓	320	✓	570	✓
35	✓	160	✓	330	✓	580	✓
40	✓	165	✓	340	✓	590	✓
45	✓	170	✓	350	✓	600	✓
50	✓	180	✓	360	✓	610	*
55	✓	190	✓	370	✓	620	✓
60	✓	200	✓	380	✓	630	✓
65	✓	210	✓	390	✓	640	*
70	✓	220	✓	400	✓	650	✓
75	✓	230	✓	410	✓	660	*
80	✓	240	✓	420	✓	670	*
85	✓	250	✓	430	✓	680	*
90	✓	260	✓	440	✓	690	*
95	✓	270	✓	450	✓	700	✓
100	✓	280	✓	460	✓		
105	✓	290	✓	470	✓		
110	✓	300	✓	480	✓		
115	✓			490	✓		
120	✓			500	✓		
125	✓			510	✓		
130	✓			520	✓		
135	✓			530	✓		
140	✓			540	✓		

Rundstahl

nach EN 10025

Qualität S355J2+AR (1.0570) gewalzt nach EN 10060 Stangenlänge ca. 4,5 – 6,5 m				Qualität S355J2G3+N (1.0570) geschmiedet n. DIN 7527 Stangenlänge ca. 4 – 6 m			
∅		∅		∅		∅	
20	✓	145	✓	300	✓	550	✓
25	✓	150	✓	310	✓	560	✓
30	✓	155	✓	320	✓	570	✓
35	✓	160	✓	330	✓	580	✓
40	✓	165	✓	340	✓	590	✓
45	✓	170	✓	350	✓	600	✓
50	✓	180	✓	360	✓	610	✓
55	✓	190	✓	370	✓	620	✓
60	✓	200	✓	380	✓	630	✓
65	✓	210	✓	390	✓	640	*
70	✓	220	✓	400	✓	650	✓
75	✓	230	✓	410	✓	660	✓
80	✓	240	✓	420	✓	670	✓
85	✓	250	✓	430	✓	680	✓
90	✓	260	✓	440	✓	690	*
95	✓	270	✓	450	✓	700	✓
100	✓	280	✓	460	✓		
105	✓	290	✓	470	✓		
110	✓	300	✓	480	✓		
115	✓			490	✓		
120	✓			500	✓		
125	✓			510	✓		
130	✓			520	✓		
135	✓			530	✓		
140	✓			540	✓		

✓ = lagernd

* = auf Anfrage