

WINKELSTAHL gleichschenkelig, rundkantig

Qualität: S235JR / EN 10025 / EN 10056 Teil 1+2
 S355J2 – auf Anfrage
 in Lagerlängen à ca. 6 m und 12 m

Abmessungen	3	4	5	6	7	8	9	10	11	12	13	15	16	20
15/15	*													
20/20	✓	*												
25/25	✓	*	*											
30/30	✓	✓	✓											
35/35	✓	✓	*											
40/40		✓	✓											
45/45			✓											
50/50		✓	✓X	✓	✓	✓								
60/60			✓	✓X		✓								
70/70					✓X		*							
80/80				*		✓X		✓						
90/90					*		✓X							
100/100						✓		✓X		✓				
120/120								✓X	✓X	✓X	*			
140/140													*	
150/150										✓		✓		
160/160												*		
200/200													✓	✓

WINKELSTAHL feuerverzinkt, gleichschenkelig

Qualität: S235JR / EN 10025 / EN 10056 / EN 1461
 in Lagerlängen à ca. 6 m

Abmessungen	25/25/3	30/30/3	35/35/4	40/40/4	40/40/5	50/50/5	60/60/6

✓ = lagernd
 * = auf Anfrage
 X = auch in 12 m Länge