

WINKELSTAHL ungleichschenkelig, rundkantig

Qualität: S235JR / EN 10025 / EN 10056 Teil 1+2

S355J2 – auf Anfrage

in Lagerlängen à ca. 6 m und 12 m

Abmessungen	3	4	5	6	7	8	9	10	11	12	13	15	16	20
30/20	*	*												
40/20	*	*												
45/30		*	*											
50/30			✓											
50/40		*	*											
60/30			✓											
60/40			✓	✓										
65/50			✓	*	*									
75/50			*	*	✓									
75/55					✓									
80/40				✓		✓								
80/60				*										
90/60				*		*								
100/50				✓		✓		✓						
100/65					✓		✓							
100/75					✓		✓		*					
120/80						✓X		✓X		✓X				
130/65						✓X		✓X						
150/75							✓X		*					
150/100								✓X		✓X				
160/80								*						
200/100								✓X		✓X				

STAHL - Wasserspulen

Ausführung: Ungestrichen, 4 mm Stahlblech
 unter 5000 mm Länge – 2 Stk. Ankerleisten
 über 5000 mm Länge – 4 Stk. Ankerleisten

Längen in mm: 3000 / 3500 / 4000 / 4500 / 5000 / 5500 / 6000

✓ = lagernd
* = auf Anfrage
X = auch in 12 m Länge