

Feinbleche kaltgewalzt / verzinkt / elo-verzinkt

DC01A - EN 10130 / EN 10131

Format / Dicke	0,50	0,75	1,00	1,25	1,50	2,00	2,50	2,99
2000 x 1000	✓	✓	✓	✓	✓	✓	✓	✓
2500 x 1250	*	✓	✓	✓	✓	✓	✓	✓
3000 x 1500	*	✓	✓	✓	✓	✓	✓	✓
4000 x 2000					✓	✓	*	✓

Feuerverzinkt DX51D+Z275MA(C) - EN 10346 / EN 10143

Format / Dicke	0,50	0,55	0,60	0,70	0,75	0,90	1,00	1,25	1,50	2,00	2,50	2,99	4,00	5,00
2000 x 1000	*	✓	*	*	✓	*	✓	✓	✓	✓	✓	✓	✓	*
2500 x 1250	*	*	*	*	✓	*	✓	✓	✓	✓	✓	✓	✓	*
3000 x 1500	*	*	*	*	✓	*	✓	✓	✓	✓	✓	✓	✓	✓
4000 x 1500					*	*	*	*	*	✓	*	✓	*	*

Elo-verzinkt DC01A+ZE25/25APC - EN 10152 / EN 10131

Format / Dicke	0,75	1,00	1,25	1,50	2,00	2,50	2,99
2000 x 1000	✓	✓	✓	✓	✓	*	*
2500 x 1250	✓	✓	✓	✓	✓	*	*
3000 x 1500	✓	✓	✓	✓	✓	✓	✓

✓ = lagernd

* = auf Anfrage