

Profile kaltgewalzt

Qualität S235JR nach EN 10025 / EN 10162

in Werkslängen von ca. 6 m, Werkzeugeignisse: 2.2 nach EN 10204/CE

U-Profile „UPG“ gleichschenkelig

Abmessungen in mm	1,5	2,0	3,0	4,0
15x15x15	✓			
20x20x20		✓		
25x25x25		✓		
30x30x30		✓	✓	
35x35x35		✓		
36x36x36			✓	
40x40x40		✓	✓	✓
50x50x50			✓	✓
60x60x60			✓	✓
70x70x70				✓

Winkelprofile „LPG“ gleichschenkelig

Abmessungen in mm	1,5	2,0	3,0	4,0
15x15	✓	✓		
20x20		✓		
25x25		✓		
30x30		✓	✓	
40x40		✓	✓	✓
50x50			✓	✓
60x60			✓	✓
70x70			✓	
80x80				✓
100x100			✓	

U-Profile „UPG“ ungleichschenkelig

Abmessungen in mm	1,5	2,0	2,5	3,0	4,0	5,0	6,0
15x30x15		✓					
20x35x20				✓			
20x40x20		✓		✓			
20x65x20		✓					
22x30x22				✓			
25x40x25				✓			
30x50x30				✓			
30x60x30				✓			
40x50x40				✓	✓		
40x60x40				✓	✓		
40x80x40				✓	✓		
50x80x50					✓	✓	
50x100x50				✓	✓	✓	✓
60x120x60					✓	✓	✓
60x140x60						✓	✓
65x160x65							✓
70x200x70							✓
75x150x75					✓		

Winkelprofile „LPG“ ungleichschenkelig

Abmessungen in mm	1,5	2,0	2,5	3,0
30x20		✓		
40x20		✓		
50x30				✓
60x30				✓
60x40				✓
80x40				✓

✓ = lagernd

leer = auf Anfrage