

## Stahlrohre schwarz längsnahtgeschweißt

nach EN 10217-1/ EN 10220, Qualität P235TR1  
Werkslängen á ca. 6 m, mit glatten Enden

Ø	Wandstärke in mm										
	2,0	2,3	2,6	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3
33,7	✓										
38,0		✓									
42,4		✓									
48,3		✓				✓					
51,0		✓									
57,0		✓									
60,3		✓							✓		
63,5			✓								
70,0			✓								
76,1			✓	✓	✓				✓		
82,5			✓								
88,9				✓	✓		✓		✓		✓
101,6				✓		✓	✓		✓		✓
108,0				✓		✓					
114,3					✓	✓			✓		
121,0							✓				
127,0							✓				
133,0							✓				
139,7							✓		✓		✓
152,4								✓			
159,0				✓			✓	✓			
168,3							✓	✓			
177,8									✓		
193,7										✓	
219,1								✓			✓
244,5											✓
273,0											✓

## Konstruktionsrohre schwarz geschweißt

nach EN 10219, Qualität S235JRH  
in Werkslängen á ca. 6 m, mit glatten Enden

Ø	Wandstärke in mm				
	2,0	2,3	2,6	2,9	3,2
22,0	✓				
25,0	✓				
27,0	✓		✓		
34,0	✓			✓	
42,0	✓				✓
48,0	✓	✓			✓
51,0		✓			
60,0	✓				✓

✓ = lagernd  
leer = auf Anfrage